



SINCE 1975<sup>®</sup>

# DSC INVERTED BUCKET TYPE STEAM TRAP



CAST IRON IB STEAM TRAP  
No : 980 SERIES  
CONN.SE:1/2"~2"  
MAX:9,000KG/HR 17KG/CM<sup>2</sup>



CAST IRON IB STEAM TRAP  
No : 991 SERIES  
CONN.FE:1/2"~3"  
MAX:9,000KG/HR 17KG/CM<sup>2</sup>



CAST IRON IB STEAM TRAP  
No : 981 SERIES  
CONN.SE:1/2"~2"  
MAX:4,500KG/HR 17KG/CM<sup>2</sup>



CAST IRON IB STEAM TRAP  
No : 991K SERIES  
CONN.FE:1/2"~2"  
MAX:4,500KG/HR 17KG/CM<sup>2</sup>



CAST IRON IB STEAM TRAP  
No : 41 SERIES  
CONN.SE:1/2"~2"  
MAX:9,000KG/HR 17KG/CM<sup>2</sup>



CAST STEEL IB STEAM TRAP  
No : 680 SERIES  
CONN.SE:1/2"~2"  
MAX:9,000KG/HR 41KG/CM<sup>2</sup>



CAST STEEL IB STEAMTRAP  
No : 680FSERIES  
CONN.FE:1/2"~2"  
MAX:9,000KG/HR 41KG/CM<sup>2</sup>



S.S IB STEAM TRAP  
No : 701~704  
CONN.SE:1/2"~1-1/2"  
MAX:2,300KG/HR 28KG/CM<sup>2</sup>



S.S IB STEAM TRAP  
No : 701F~706F  
CONN.FE:1/2"~2"  
MAX:9,000KG/HR 28KG/CM<sup>2</sup>



S.S IB STEAM TRAP  
No : 701S  
CONN.SE:1/2"~1"  
MAX:470KG/HR 28KG/CM<sup>2</sup>



S.S IB STEAM TRAP  
No : 771~772  
CONN.SE:1/2"~1"  
MAX:930KG/HR 28KG/CM<sup>2</sup>



S.S IB STEAM TRAP  
No : 771~772  
CONN.SE:1/2"~1"  
MAX:930KG/HR 28KG/CM<sup>2</sup>



S.S IB STEAM TRAP  
No : 771~772  
CONN.FE:1/2"~1"  
MAX:930KG/HR 28KG/CM<sup>2</sup>



S.S IB STEAM TRAP  
No : 741~746  
CONN.SE : 1/2"~2"  
MAX: 30KG/CM<sup>2</sup>



S.S IB STEAM TRAP  
No : 780~781  
CONN.SE:1/2"~1"  
MAX:500KG/HR 41KG/CM<sup>2</sup>



S.S IB STEAM TRAP  
No : 780F~781F  
CONN.FE:1/2"~1"  
MAX:500KG/HR 41KG/CM<sup>2</sup>



FORGED STEEL & S.S316 IB  
STEAM TRAP  
No : 642~946F  
CONN.SE:1/2"~2"  
MAX:8,600KG/HR 69KG/CM<sup>2</sup>



FORGED STEEL & S.S316 IB  
STEAM TRAP  
No : 941 & 941F  
CONN.SE:1/2"~1"  
MAX:400KG/HR 69KG/CM<sup>2</sup>



FORGED STEEL & S.S316 IB  
STEAM TRAP  
No : 951~951F  
CONN.FE:1/2"~1"  
MAX:400KG/HR 69KG/CM<sup>2</sup>



FORGED STEEL IB  
STEAM TRAP  
No : 1543~2545  
CONN.FE:1/2"~2"  
MAX:8,600KG/HR 183KG/CM<sup>2</sup>



DUAL ORIFICE STEAM TRAP  
No : 911D~996D  
CONN.SE:1/2"~2"  
MAX:9,000KG/HR 17KG/CM<sup>2</sup>



DSC PATENT CHECK VALVE  
FOR IB STEAM TRAP  
CONN.SE : 1/2"~2"



DSC STEAM TRAP BUCKET



DSC F22 FLOAT AND LEVER



DUCTILE IRON F&T  
STEAM TRAP  
No : F2~F08  
CONN.SE : 1/2"~2"  
MAX:590KG/HR 17KG/CM<sup>2</sup>



DUCTILE IRON F&T  
STEAM TRAP  
No : F2F~F08F  
CONN.FE : 1/2"~2"  
MAX:590KG/HR 17KG/CM<sup>2</sup>



DUCTILE IRON F&T  
STEAM TRAP  
No : F22  
CONN.SE : 1/2"~1"  
MAX:590KG/HR 17KG/CM<sup>2</sup>



DUCTILE IRON F&T  
STEAM TRAP  
No : F12  
CONN.SE : 3"~4"  
MAX:92 TON/HR 17KG/CM<sup>2</sup>



CARBON STEEL F&T  
STEAM TRAP  
No : FS2~FS08  
CONN.SE : 1/2"~2"  
MAX:9,500KG/HR 30KG/CM<sup>2</sup>



CARBON STEEL F&T  
STEAM TRAP  
No : FS2F~FS08F  
CONN.FE : 1/2"~2"  
MAX:9,500KG/HR 30KG/CM<sup>2</sup>



CARBON STEEL F&T  
STEAM TRAP  
No : FS12H  
CONN.FE : 3"~4"  
MAX:92 TON/HR 30KG/CM<sup>2</sup>



S.S F&T STEAM TRAP  
No : FSS5~FSS08  
CONN.SE : 1/2"~2"  
MAX:9,500KG/HR 30KG/CM<sup>2</sup>



S.S F&T STEAM TRAP  
No : F77  
CONN.SE : 1/2"~1"  
MAX:590KG/HR 17KG/CM<sup>2</sup>



S.S F&T STEAM TRAP  
No : F77  
CONN.SE : 1/2"~1"  
MAX:590KG/HR 17KG/CM<sup>2</sup>



S.S F&T STEAM TRAP  
No : F77  
CONN.FE : 1/2"~1"  
MAX:590KG/HR 17KG/CM<sup>2</sup>



DSC THERMOSTATIC  
CAPSULE



DSC S.S FLOAT



S.S VACUUM BREAKER  
No : VB1  
CONN.SE : 1/2"  
MAX: 9KG/CM



THERMOSTATIC  
No : S61  
CONN.SE : 1/2"~1"  
MAX:1,200KG/HR 22KG/CM<sup>2</sup>



THERMOSTATIC  
No : S61F  
CONN.FE : 1/2"~1"  
MAX:1,200KG/HR 22KG/CM<sup>2</sup>



THERMOSTATIC  
No : S70  
CONN.SE : 1/4"~3/4"  
MAX:1,200KG/HR 22KG/CM<sup>2</sup>



THERMODYNAMIC  
No : D60  
CONN.SE : 1/2"~1"  
MAX:1,200KG/HR 40KG/CM<sup>2</sup>



THERMODYNAMIC  
No : D60F  
CONN.FE : 1/2"~1"  
MAX:1,200KG/HR 40KG/CM<sup>2</sup>



AIR VENT  
No : A1~A6  
CONN.SE : 1/2"~2"  
MAX: 17KG/CM<sup>2</sup>



AIR VENT  
No : 11AV~13AV  
CONN.SE : 1/2"~1"  
MAX: 28KG/CM<sup>2</sup>



AIR VENT  
No : 33AV  
CONN.SE : 1/2"~2"  
MAX:1,200KG/HR 40KG/CM<sup>2</sup>



No : CPT  
CONN.SE : 1/2"~2"  
MAX: 17KG/CM<sup>2</sup>



No : CPF  
CONN.FE : 1-1/2"~10"  
MAX: 17KG/CM<sup>2</sup>