

**Maintenance-free
metallic-seat
non-return valves**



flanged

**PN 6, 16
DN 15-350**

Application

- Warm-water heating systems DIN 4751
- Hot-water heating systems DIN 4752
- Heat-transfer installation DIN 4754
- Pressure vessel equipment to TRB 801 nr. 45¹⁾
- Boiler installations to TRD 108/110¹⁾

¹⁾ Please contact KSB for limitations imposed by the applicable technical codes.

Operating data

- Temperature range:
 - 10 up to +300 °C for EN-GJL-250 *)
 - 10 up to +350 °C for EN-GJS-400-18-LT **)
 - 30 °C for EN-GJS-400-18-LT **) with bolts for low-temperature service
- Pressure range:
 - Straight way pattern up to $\Delta p = 6$ or 16 bar
 - Angle pattern up to $\Delta p = 16$ bar

Materials

Body:

- Straight-way pattern:
 - Cast iron with flake graphite EN-GJL-250 *)
 - Cast iron with nodular graphite EN-GJS-400-18-LT **)
- Angle pattern:
 - Cast iron with flake graphite EN-GJL-250 *)
- For further details, see table of materials

Design

- Straight-way or angle pattern with horizontal seat
- With spring-loaded check cone
- Free from asbestos, CFC, PCB
- Exterior finish: blue similar to RAL 5002

The valves meet the safety requirements of the Pressure Equipment Directive 97/23/EC (PED) of annex I for fluids of the groups 1 and 2.

Standard variants

- Oil and grease-free design
- Other flange design

Remarks

- Operating instructions: 0570.8

On all enquiries/orders please specify

Non-return valve

1. BOA[®]-R according to type series booklet 7117.1
2. PN 6 or 16
3. EN-GJL-250 *) or EN-GJS-400-18-LT **)
4. Straight-way and angle pattern (angle pattern only EN-GJL-250 *)
5. DN 15-350 (DN 350 only in EN-GJS-400-18-LT **)
6. Standard variants

*) previously: GG-25

***) previously: GGG-40.3

The valves do not have a potential internal source of ignition and can be used in potentially explosive atmospheres, group II, category 2 (zones 1+21) and category 3 (zones 2+22) according to ATEX 94/9/EC.



Working pressures


Material	Nominal pressure PN	Body pressure test with water Body ¹⁾	Seat leakage test with water Seat ²⁾	Working pressures in bar at temperatures in °C ³⁾ to V-DIN 2401 (1.66)				
				- 10 up to +120	200	250	300	350
EN-GJL-250	6	9	7,6	6	5	5	5	-
	16	24	17,6	16	12.8	11.2 ⁴⁾	9.6 ⁴⁾	-
EN-GJS-400-18-LT	16	24	17,6	16	14.7	13.9 ⁴⁾	12.8 ⁴⁾	11.2

¹⁾ DIN 3230-BQ (ISO 5208)

²⁾ DIN 3230-BN/leak rate 1 (ISO 5208/rate A)

³⁾ For intermediate temperatures use linear interpolation.


⁴⁾ Note: the connection bolts between valve and pipe flange must also have a guaranteed hot yield strength (e.g. material 5.6 or CK 35 V).




Materials

Part no.	Name of parts	PN	DN	Material	Material no.
100	Body	6/16	15-300	EN-GJL-250	JL 1040
		16	15-350	EN-GJS-400-18-LT	JS 1025
161	Body cover	6/16	15-300	EN-GJL-250	JL 1040
		16	15-350	EN-GJS-400-18-LT	JS 1025
351	Check cone	6	15-175	X 20 Cr 13	1.4021
		16	15-175		
		6	200	St, seat X 15 CrNi 18 8	1.4301
		16	200-350	Guide pin X 20 Cr 13	1.4021
411	Gasket			CrNiSt-graphite	
515	Seat ring			X 20 Cr 13	1.4021
902	Stud		250-300	CK 35 V for EN-GJL-250	
			15-350	CK 35 V for EN-GJS-400-18-LT	
920	Nut		15-350	C 35	
950	Spring			X 12 CrNi 17 7 (1.4310)	1.4310

Dimensions



Straight-way pattern



Angle pattern

		Dimensions (mm)								Weight (kg) approx.	
PN	DN	l ₁	l ₂	h ₁	h ₂	D	ø k	n x d ₃	C	Straight-way pattern kg	Angle pattern kg
6 ¹⁾ JL1040	15	130	-	50	-	95	55	4 x 11	14	2.3	-
	20	150	-	60	-	105	65	4 x 11	16	3.5	-
	25	160	-	65	-	115	75	4 x 11	16	4.0	-
	32	180	-	85	-	140	90	4 x 14	18	6.9	-
	40	200	-	90	-	150	100	4 x 14	18	8.0	-
	50	230	-	95	-	165	110	4 x 14	20	10.5	-
	65	290	-	120	-	185	130	4 x 14	20	16.8	-
	80	310	-	130	-	200	150	4 x 19	22	22.0	-
	100	350	-	155	-	220	170	4 x 19	24	32.5	-
	125	400	-	175	-	250	200	8 x 19	26	52.0	-
16 JL1040 JS1025	15	130	90	50	25	95	65	4 x 14	14	2.3	2.2
	20	150	95	60	35	105	75	4 x 14	16	3.5	3.2
	25	160	100	65	35	115	85	4 x 14	16	4.0	4.1
	32	180	105	85	50	140	100	4 x 19	18	6.9	6.9
	40	200	115	90	50	150	110	4 x 19	18	8.0	8.0
	50	230	125	95	60	165	125	4 x 19	20	10.5	10.2
	65	290	145	120	70	185	145	4 x 19	20	16.8	16.1
	80	310	155	130	75	200	160	8 x 19	22	22.0	19.5
	100	350	175	155	95	220	180	8 x 19	24	32.5	30.3
	125	400	200	175	105	250	210	8 x 19	26	52.0	45
150	480	225	195	110	285	240	8 x 23	26	72.0	64.5	
200	600	275	245	140	340	295	12 x 23	30	123.0	108	
250	730	325	295	150	400	355	12 x 28	32	200.0	170	
300	850	300	335	185	460	410	12 x 28	32	310.0	262	
350 ²⁾	980	-	335	-	520	470	16 x 28	36	357.0	-	

¹⁾ Pattern of drilled holes to PN 6 (dimensions k and nxd); however, flanges dimensioned to PN 16 (dimensions D and b). Please take this into account when selecting the flange connecting bolts.

²⁾ DN 350 only in EN-GJS-400-18-LT (previously: GGG-40.3) in straight-way pattern on request

Installation instructions

Observe direction of flow and integral direction arrow.
For opening, a minimum pressure is required. If this pressure is not attained, the installed closing spring can be removed.
Valves without a closing spring can only be installed upright in horizontal pipelines.

Minimum opening pressures (bar)

DN	15-50	65-150	200-350
With spring	0.250	0.200	0.150
Without spring	0.025	0.016	0.022

Connection dimensions - Standards:

Flanges: DIN EN 1092-2, type of flange 21 - JL1040
type of flange 21-2 - JS1025

Raised faces: DIN EN 1092-2, type B

Face-to-face dimension:


Straight-way pattern: EN 558-1/1 (previously: DIN 3202/F 1)
ISO 5752/1

Angle pattern: EN 558-1/8 (previously: DIN 3202/F 32)
ISO 5752/8

Gasket of
pure graphite,
asbestos-free

Closing spring
of stainless spring
steel

Check cone of
stainless steel
or steel with
stainless guide
pin and alloyed
sealing surface



Subject to technical modification without prior notice